


# STAINLESS STEEL ROUND METAL BUTTON STYLE Vandal-Proof Intercom Lobby Panels

*A stainless steel, round metal button,  
vandal-proof panel with stylish good looks!*

**WITH PERMANENTLY ENGRAVED NUMBERSTRIPS**




**CS-006E**

(Shown with optional Engraved building address and optional engraved 'LDDS' Lee Dan Directory Strips)

**NOTE: Wherever shown, Directory Strips are optional.**

- Optional building address engraving foils theft (add suffix 'E' to model no.)
- **Standard Centurion™ Features:**
- High grade 16 gauge (low carbon) Stainless Steel.
- Integral Stainless Steel/Lexan® sheet directory.
- Exclusive 3-layer metal speaker baffle.
- Mylar cone weatherproof loudspeaker.
- Heavy (6 amp rated) solid metal buttons with positive screw terminals.
- Permanently, custom engraved plastic numberstrips.
- Custom sizing available.
- 'Tampruf' tamper-proof access screws.
- Available with any number of buttons.



**CM-044P**  
Speaker/Mic panel. Shown with optional P.O. release switch.

**NOTE: P.O. switch is NOT USPS approved. Use is subject to approval by local postmaster.**

Speaker at Top  
P.O. switch in middle. Mic shown at bottom.

**CENTURION™ Stainless Steel, Round Metal Button, Numberstrips, Loudspeaker\* (L/S) Lobby Panels**

\*Optional speaker equipment is available, including Bell/Buzzer, Speaker/Transmitter, Speaker/Microphone, Amplified Handset, and Speaker/Transmitter Handset. Please consult Lee Dan for wall dimensions of any Centurion™ panels other than 'CS' loudspeaker type. Contact Lee Dan for other styles including economy, vandal-resistant, oversized directory and solid polished brass.

Number of Buttons	ALL PANELS OUTSIDE DIMENSIONS		FLUSH PANELS WALL OPENING			DIRECTORY INFO	
	High	Wide	Flush Backbox	High	Wide	Maximum Names	Strip Capacity
2-6	11-1/2"	5"	BB-101	10-1/8"	4-1/8"	9	11
7-16	18-3/4"	5"	BB-201	16-1/8"	4-1/8"	19	21
17-36	18-3/4"	10"	BB-202	16-1/8"	8-1/8"	50	53
37-46	18-3/4"	14"	BB-203	16-1/8"	12-1/8"	50	53
47-82	18-3/4"	18"	BB-204	16-1/8"	16-1/8"	100	106
83-96	18-3/4"	22"	BB-205	16-1/8"	20-1/8"	100	106
97-128	18-3/4"	26"	BB-206	16-1/8"	24-1/8"	150	159
129-144	18-3/4"	30"	BB-207	16-1/8"	28-1/8"	150	159

For CENTURION™ Panels Over 144 Buttons, Please Call LEE DAN®

800-231-1414 • 631-231-1414  
155 Adams Avenue • Hauppauge, NY 11788-3699  
www.LEEDAN.com • Fax 631-231-1498

INTERCOMS • CCTV • MAILBOXES • DIRECTORIES  
ANNUNCIATORS • WIRE & CABLE • NURSE-CALL

With continuous product improvement, specifications are subject to change without notice.

**ARCHITECTS' & ENGINEERS' SPECIFICATIONS**

**“Centurion™” Lobby Panel:** Intercom panel shall be a Lee Dan vandal-proof Centurion™ series or approved equal. Panel shall be constructed of 16 gauge low-carbon Stainless Steel. Pushbuttons shall be heavy 6 amp rated, chrome plated, solid brass, round metal buttons. Pushbutton connections must be made by positive screw terminals by circuit board. Pigtail connections will not be acceptable. Apartment numbers shall be permanently engraved on individually replaceable numberstrips. Building address shall be permanently engraved at the top of the lobby panel.

Speaker shall be 3.5", 1 Watt, 45 Ohm with mylar cone. Paper cone speakers are not acceptable. Speaker shall be protected by a three (3) layer metal speaker baffle. Intercom panel shall include an integral alphabetical directory protected by Lexan® sheet. Speaker, pushbuttons and directory components shall all be field replaceable. Glued in place components are not acceptable. Mounting screws shall be tamper resistant Tampruf type. A Lee Dan model SC-T Tampruf type screw driver shall be provided with each lobby panel for directory maintenance.

Lexan® is a registered trademark of General Electric.

**IR-204E Apartment Stations (option 1 of 3\*):** Suite stations shall be Lee Dan model IR-204E or approved equal. Stations shall be molded in white, high impact ABS plastic. Individual pushbutton controls shall be provided for Talk, Listen, and Door release functions. Button identification shall be provided in English, braille, and by symbols. Pushbuttons shall be self-wiping type with positive screw terminals. Pigtail connections are not acceptable. Speaker shall be 2.5", .3 Watt, 45 Ohm. Pushbuttons and speakers shall be field replaceable. Glued in place components are not acceptable. Mounting screws shall be tamper resistant Scrulox type.

**IR-464SS Apartment Stations (option 2 of 3\*):** Suite stations shall be Lee Dan model IR-464SS or approved equal. Heavy duty 6 amp rated, chrome plated, solid brass, round metal buttons shall be provided for TALK, LISTEN, and DOOR operations. Pushbutton connections must be made by positive screw terminals by circuit board. Pigtail connections are not acceptable. Stations shall be permanently stamped with TALK/LSTN/DOOR legends for tenant operation. The speaker/microphone shall be a mylar cone high sensitivity type with voice-frequency response. Paper cone speakers are not acceptable. Speaker shall be protected by a double metal speaker baffle. Station shall be constructed of 18 gauge stainless steel. Mounting screws shall be tamper resistant Scrulox type.

**IR-444 Apartment Stations (option 3 of 3\*):** Suite stations shall be Lee Dan model IR-444 or approved equal. Momentary action, self-wiping pushbuttons shall be provided for TALK, LISTEN, and DOOR operations, with 5/16" thick solid aluminum plungers. Connections shall be made by positive screw terminals. Pigtail connections shall not be acceptable. Stations shall be permanently stamped with DOOR/LSTN/TALK legends for tenant operation. The speaker/microphone shall be a mylar cone high sensitivity type with voice-frequency response. Paper cone speakers are not acceptable. Speaker shall be protected by a double metal speaker baffle. Station shall be made of 20 gauge stainless steel. Mounting screws shall be tamper resistant Scrulox type.

\*Choose from more than 70 different stations. Request brochure A-101.

**Amplifier:** Intercom amplifier shall be Lee Dan model PK-543A or approved equal. Amplifier shall be powered by a Lee Dan model PS-30A pigtail transformer (16VAC/30VA), or approved equal, which shall be UL listed.

**Other Accessories**




- Engraving** Ask for engraving brochure A-107.
- JB-200** Amplifier Junction Box.
- Rain-Guard** Weather Hood. Ask for brochure IN-004.
- SC-T** ‘Tampruf’ type tamper screwdriver.

**Other LEE DAN® Panel Styles**



**Bravo™**

Solid Polished Brass  
• 3 Versions




**Style “E”™**  
Economy Style


**Van-Guard®**  
Extruded Alum.  
Engraved Plungers



**Millennium™**  
Stainless Steel  
Black Buttons



**Quantum™**  
St. Steel  
Engraved  
Faceplate




**Regency™**  
Extruded  
Aluminum  
Oversized  
Directory


**Popular Apartment Stations**



**IR-204E**  
Plastic  
Surface Mount



**IR-464SS**  
St. Steel  
Requires Housing



**IR-444**  
St. Steel  
Surface