

Audio Evacuation Ceiling Speakers and Strobes Genesis Series



Genesis life safety ceiling speakers are small, compact, audible emergency signaling devices. Protruding no more than 1.6" (41mm) from the ceiling, Genesis speakers feature textured housings in neutral white or life safety red.

Edwards Genesis speakers feature 1/4 W to 2 W operation that is selectable with a conveniently located switch. The wattage tap setting remains clearly visible and locked into place after final installation.

All Genesis ceiling speakers include a DC blocking capacitor to allow electrical supervision of the audio distribution circuit.

Features and Specifications

- Low profile design
- Red or white housings
- 1/4, 1/2, 1, and 2 watt selections via switch
- Up to 100dB @ 1m/90dB @ 10ft. output
- Fits all standard 4" square electrical boxes – no extension ring or trim plate required
- Operating temperature range: 32°F to 120°F (0°C to 49°C)

Ordering Information

Description	Cat. No.	Operating Voltage	Wattage Taps	dB at 1m/10ft.	Marking	Housing Color
Field Configurable Ceiling Speaker	EGC-S2	25V RMS	0.25, 0.5, 1.0, 2.0	90-100/80-90	None	White
	EGCF-S2	25V RMS	0.25, 0.5, 1.0, 2.0	90-100/80-90	FIRE	White
	EGCFR-S2	25V RMS	0.25, 0.5, 1.0, 2.0	90-100/80-90	FIRE	Red
	EGC-S7	70V RMS	0.25, 0.5, 1.0, 2.0	90-100/80-90	None	White
	EGCF-S7	70V RMS	0.25, 0.5, 1.0, 2.0	90-100/80-90	FIRE	White
	EGCFR-S7	70V RMS	0.25, 0.5, 1.0, 2.0	90-100/80-90	FIRE	Red

Weights and Dimensions

Cat. No.	Approx. Shipping Weight (lb.)
EGC-S2	1.62
EGCF-S2	1.62
EGCFR-S2	1.62
EGC-S7	1.62
EGCF-S7	1.62
EGCFR-S7	1.62



One or more patents pending.



Distributed By: Lee Dan Communications, Inc.
www.leedan.com info@leedan.com Toll-Free 1-800-231-1414