



Accessories

AH-108, AH-16TN, AH-32TN

For Intercom, Paging and Paging/Talkback Systems

AH-108

**Features:**

- 8Ω, 10W horn with built-in non-polarized capacitor
 - All metal weather proof construction for indoor or outdoor use
 - Universal swivel mount base
 - Beige baked enamel finish
- **Use with Mid-power (MP-S) system for two-way communication. Can also be used with LEF and NEM systems.**

Specifications:

- Power Handling Capacity: 10 Watts (Continuous)
Impedance: 8Ω
Frequency Response: 300-10,000 Hz
Dispersion Angle: 120°
Sound Pressure Level: 110dB at rated output measured on 4' axis
Sensitivity as a microphone: -26dBm
(Re: 10 dynes/cm²)
Dimensions: 6-1/8" Bell x 6-1/2" Deep

AH-16TN

**Features:**

- Built-in 70V transformer, providing 1, 2, 4, 8, & 16 Watt taps, + 8Ω direct
 - High intelligibility, used for paging into large or high noise areas
 - All metal weather proof construction for indoor or outdoor use
 - Screwdriver selectable wattage taps
 - Universal swivel mount base
 - Beige baked enamel finish
- **Use with High-power (AP-M) system, set on 8Ω tap for two-way communication (add NP-25V capacitor or NP-B call button).**

Specifications:

- Power Handling Capacity: 16 Watts (Continuous)
Impedance: 8Ω Direct, or 25/70.7V transformer
Wattage Taps: 25V: 0.5/1/2/4/8
70.7V: 1/2/4/8/16
Frequency Response: 350-15,000 Hz
Dispersion Angle: 130°
Sound Pressure Level: 119dB at rated output measured on 4' axis
Sensitivity as a microphone: -28dBm
(Re: 10 dynes/cm²)
Dimensions: 8-1/8" Bell x 9" Deep

AH-32TN

**Features:**

- Built-in 70V transformer, providing 2, 4, 8, 16 & 32 Watt taps
 - High intelligibility, used for paging into large or high noise areas
 - All metal weather proof construction for indoor or outdoor use
 - Screwdriver selectable wattage taps
 - Universal swivel mount base
 - Beige baked enamel finish
- **Use with 70V paging systems**

Specifications:

- Power Handling Capacity: 32 Watts (Continuous)
Impedance: 8Ω Direct, or 25/70.7V transformer
Wattage Taps: 25V: 1/2/4/8/16
70.7V: 2/4/8/16/32
Frequency Response: 325-15,000 Hz
Dispersion Angle: 130°
Sound Pressure Level: 124dB at rated output measured on 4' axis
Sensitivity as a microphone: -28dBm
(Re: 10 dynes/cm²)
Dimensions: 8-1/8" Bell x 9" Deep