

JKW-IP Sets

DOOR **1** → INSIDE **1** → PC **10**
 Max. 20 sets

FOR Installing **New** or **Additional**
 JK Systems:

FOR **Previously** installed
 JK Systems:

JKS-IPED Boxed Set



JK-DA Plastic, surface mount door station
 JK-1MED Master station with memory
 JKW-IP Network Adaptor
 Power supply & Software CD

JKS-IPEV Boxed Set



JK-DV Zinc, surface mount door station
 JK-1MED Master station with memory
 JKW-IP Network Adaptor
 Power supply & Software CD

JKS-IPEF Boxed Set



JK-DVF Stainless steel, flush mount door station
 JK-1MED Master station with memory
 JKW-IP Network Adaptor
 Power supply & Software CD

JKW-IP



JKW-IP Network Adaptor
 Software CD
 Adaptor can be used with
 either the JK-1MED or JK-1MD

Specifications

Power source	18V DC - PS-1820UL (included with Boxed Sets), JKW-IP power supplied by JK Series Master
Consumption	Max. 200mA
Software	JKW-IP Software and updates included with JKW-IP Network Adaptor at no additional cost Processor: 2GHz or faster, RAM: minimum 1GB, Storage: 10MB or more (additional memory required for movie recording), Sound Card: 8-bit full duplex - Direct sound compatible, Display: 1024 x 786 or higher, Runtime: Microsoft® .NET framework 2.0 or later, Network: Wired 100Base-TX recommended Operating System: Windows® XP (SP3), Windows® Vista (SP1)
Protocol	TCP/IPv4, UDP/IPv4, SIP, etc
Network bandwidth	320k-8Mbps
Compatibility	JK-1MED with memory JK Master Station, JK-1MD JK Master Station
Languages	English, French, Spanish, Japanese, German, Italian, Dutch

Optional Input device specifications

Input method	N/O or N/C dry closure contact (start signal only detection method)
Detection confirmation time	100mS or more
Contact resistance	Closed circuit: 700Ω or less Open circuit: 3KΩ or more

Optional Output device specifications

Output method	Dry contact (N/O)
Relay Contact Rating	AC 24V 0.5A (resistive load) DC 24V 0.5A (resistive load)

Unit Dimensions

