PARCEL LOCKERS

FRONT LOADING MODEL 562

REAR LOADING MODEL 563

SPECIFICATIONS

Doors are fabricated from 1/8" thick aluminum plate and have a contiuous hinge for the entire height of the door. Rear loading model is equipped with a lift off cover. Each door has a dual lock mechanism that retains the tenant key until released by the postal control key. Door lock is a 5-pin cam lock and the key retainer lock is either an Arrow postal service lock or a Master dead bolt lock. Parcel lockers are compatible in size and construction and include trim to form an integral unit with the mailboxes and mail collection units. Standard finish is 628 natural anodized aluminum: optional finishes - see page 3.

Minimum wall depth 16 1/2"

Recessed or Full Surface Mounting *

Permit the use of automatic-locking street entrance doors for apartments. Maintain security, but allow mailman to enter the building to distribute mail in conformance with U.S.P.S. regulations.

MODEL 5620 – Loose key type prepared for U.S.P.S. lock (standard)

MODEL 5621 – With key retractor and 24" chain only, prepared for U.S.P.S. lock

MODEL 5622 – Same as 5620 with 5-pin cam lock no. 6708

MODEL 5623 – Same as 5621 with 5-pin cam lock no. 6708

MODEL 5624 – Same as 5620 but prepared to receive Medeco 5-pin cam lock supplied by customer for installation by Bommer

MODEL 5624 – Same as 5621 but prepared to receive Medeco 5-pin cam lock supplied by customer for installation by Bommer

* Use 5641 full surface frame for surface mounting



Model 562-72 (Shown next to model 6230-74 rear-loading mailboxes)

PARCEL LOCKER DOORS ARE AVAILABLE IN A VARIETY OF COMPARTMENT SIZES:

P2 – 10 1/2" high x 12 1/2" wide x 15 1/2" deep

P3 – 16" high x 12 1/2" wide x 15 1/2" deep

P4– 21 1/2" high x 12 1/2" wide x 15 1/2" deep

P5 – 27 " high x 12 1/2" wide x 15 1/2" deep

 $P6 - 32 \, 1/2"$ high x 12 1/2" wide x 15 1/2" deep

P7 – 38" high x 12 1/2" wide x 15 1/2" deep

SPECIFICATIONS

FINISH

- 628 natural anodized aluminum (standard)
- · Optional finishes see page 3

DIMENSIONS

• Frame size – 4 3/4" high x 6 3/8" wide

Door size – 2 3/4" high x 4 3/8" wide

 Wall cutout size – 3" high x 4 3/4" wide x 1 3/4" deep

