

MODEL 1150 1/2-HP Overhead Gate Operator

Maximum gate height 14-feet

The Model 1150 is designed to operate overhead type vehicular gates that are mounted on jamb track or jamb type hardware. The low profile and quiet operation of the 1150 make it ideal for underground parking control applications.





Standard Features

- 1/2 HP continuous duty motor
- Operates gates up to 8, 10, 12 or 14 feet high
- 40:1 gear reducer
- Direct driven limits
- Heavy-duty 3-inch rails
- #40 drive chain
- Quick release
- Shock mounts
- Plug-in loop detectors
- Built-in timer
- Gate Tracker reporting output provides operator data to access control system* (*DKS systems with card access only)
- 5-year limited warranty

Options

- The 1150 can be ordered with 4 different rail lengths to operate gates from 8 to 14 feet high
- Plug-in loop detectors
- Gate operator control stations
- Secondary entrapment prevention devices are required with this gate operator. Refer to Section 3, Pg 9-11 for selection of devices.

Dimensions	Shipping Weight	Class	Power
1150 for 8 ft. high gate 10.5"H x 21"W x 149"L	150 Lbs.	Class: II, III, IV	115 VAC, 60 Hz 5.4 A
1150 for 10 ft. high gate 10.5"H x 21"W x 173"L	160 Lbs.		
1150 for 12 ft. high gate 10.5"H x 21"W x 197"L	173 Lbs.		
1150 for 14 ft. high gate 10.5"H x 21"W x 221"L	198 Lbs.		

P/N	Description	Rail Options			
	Decomption	8 Ft.	10 Ft.	12 Ft.	14 Ft.
	Overhead Gate Operator Assembly				
1150-080	Powerhead Assembly				
1150-225	8 Ft. Rail assembly for 8 ft. high gates.				
1150-226	10 Ft. Rail assembly for 10 ft. high gates.				
1150-227	12 Ft. Rail assembly for 12 ft. high gates.				
1150-228	14 Ft. Rail assembly for 14 ft. high gates.				

1150 Overhead Gate Operator Assembled – 8 Ft. High Gates				
P/N	Description			
1150-084	Overhead Gate Operator with 8 ft. Rail Fully Assembled.	(Note 1)		

Accessories		
P/N	Description	
9409-010	DoorKing plug-in 2-channel detector. Use with DKS operators only.	
9410-010	DoorKing plug-in single channel detector. Use with DKS operators only.	

To Order: Select the powerhead and the required rail assembly.

Notes:

(1) To protect against freight damage and to reduce freight cost, the 1150 operator is shipped in two pieces; the powerhead assembly and the rail assembly. As an option for will call customers only, this version is fully assembled and ready for installation.