

MODEL 1808

The model 1808 is an ideal telephone entry system that is suited for applications that have limited space and can be used in residential as well as commercial applications. Visitors are easily identified by voice communication and can be granted or denied access directly from a touch-tone telephone.





Standard Features

- Full-Duplex Communication
- 1000 Phone Number Memory
- Programmable directory codes (1-4 digits)
- 10 and 11 digit dialing capability
- Push to Call model dials a preprogrammed phone number and visitors can enter a directory code on the keypad to call other numbers
- 5-Digit entry codes (6) for special needs
- Built-in clock provides automatic relay activation
- Time zone restrictions on selected entry codes
- Time clock has its own backup power source
- Flash entry codes
- 2 relays for door/gate control
- EEPROM Memory
- Power transformer included
- 2-year warranty

Options

- Available with small built-in directory (not lighted).
- Available in surface mount style only.
- CCTV camera (may require purchase of additional CCTV equipment).
- Mounting posts.

Dimensions	Shipping Weight	Regulatory	Power
Surface Mount: 7.375"H x 11"W x 6.375"D		FCC (US): DUF6VT-12874-OT-T DOC (CAN): 1736 4528 A ETL Listed	16 VAC, 20 VA, 250 ma Ringer Equivalence: 0.0 A Jack Type: RJ11C or W

1808 Telephone Entry System with 1000 Memory				
P/N	Description			
1808-084	Surface Mount, Hands Free	(Note 2)		
1808-082	Surface Mount, Hands Free with Directory	(Note 1, 2)		
Accessories (refer to indicated page for further description)				
P/N	Description			

P/N	Description	
1812-145	CCTV Camera Kit (pg 36)	
2600-584	Heater Kit (pg 34)	

Notes:

Directory can hold up to 10 names, depending on type size and font.
1000 Memory included.