
# **MODEL 9070 Slide Gate Operator**

#### For gates up to 22-feet long, 500 Lb, maximum gate weight

The model 9070 slide gate operator is designed to operate vehicular sliding gates in residential or light duty commercial applications only. The operator kit includes chain brackets, hardware and 20-feet of #41 chain.



### **Standard Features**

- 1/2 HP continuous duty motor
- For gates up to 22-feet, 500 Lb.
- Self-adjusting, maintenance free limits
- Programming switches allow you to set desired mode of operation
- Fail-safe design
- Auto-close timer
- Plug-in loop detectors
- 2 convenience outlets
- 5-year limited warranty
- 10°F to 140°F (-12°C to 62°C)

## **Options**

- Fail-secure keyed release
- #40 chain
- Nickel plated chain
- Stainless steel chain
- Gate operator control stations
- Post mount base plate
- Heater kit (recommended when temperature routinely falls below 32°F (0°C).
- Plug-in loop detectors
- Slide gate accessories
- Secondary entrapment prevention devices are required with this gate operator. Refer to Section 3, Pg 9-11 for selection of devices.

Dimensions	Shipping Weight	Class	Power
9070 12"w x 24"H x 11.5"D	93 Lbs.	Class: I, II	115 VAC, 60 Hz 1/2 HP: 5.4 A

9070 Slide Gate Operator			
P/N	Description		
9070-080	Slide Gate Operator, 1/2 HP, 115 VAC		
Accessorie	es		
P/N	Description		
9409-010	DoorKing plug-in 2-channel detector. Use with DKS operators only.		
9410-010	DoorKing plug-in single channel detector. Use with DKS operators only.		
1601-154	Heater Kit Heater kit for operators installed in cold weather environments. Built-in fan and thermostat.		
2600-418	Base plate to post mount the operator. Posts not included.		
2600-441	20-feet #41 chain and two master links.		
2600-862	Fail-Secure Lock Kit (Note 2)		

#### Notes:

(1) Changes operator from fail-safe to fail -secure operation. Includes keyed release to open gate upon power outage.