



Electronic Telecode[®] Relay

B-ER-2000

FEATURES

- > Hardwired unit
- > Injected molded enclosure
- > Strain relief grommets on wiring entrances
- > AC or DC activating voltage

SPECIFICATIONS

- > UL 2017 Listed
- > Registered with the FCC in compliance with Part 68 of FCC Rules and Regulations (No. 329USA-21250-RG-N)

www.leedan.com info@leedan.com Toll-Free: 800-231-1414

The Edwards B-ER-2000 Electronic Telecode Relay is designed to activate remote extension signals such as horns, bells, strobes, or similar devices. The relay is activated by the line ringing voltage of the telephone; operation of the connected signal matches the telephone ringing cycle. The unit is designed for indoor use only.

The unit mounts to any flat surface using the supplied hardware. All telephone, power input, and signal output connections are made internal to the unit.

For areas where ambient noise levels are high or where personnel are unable to be near telephones at all times. Recommended for factories, loading docks, assembly areas, lumber yards, and gas stations.

FEATURES

- > REN No: 1.5B @ > 50V; 3.4B @ < 50V
- > AC activation voltage: 10 - 250V
- > Ringing frequency: 16 to 70 Hz
- > Contact rating: 5 amps at 120V AC
- > DC keying voltage: 10-150V

