


# FireShield™ Remote Relay Module

## FSRRM



[www.leedan.com](http://www.leedan.com) [info@leedan.com](mailto:info@leedan.com) Toll-Free: 800-231-1414

## FEATURES

- > Five Form C relays rated at 1 amp each, 30V DC
- > Functions in zone relay mode or common system mode
- > Compatible with 3, 5 and 10 zone panels

The Edwards FSRRM Remote Relay Module is one component of the system that sets the FireShield ahead of its class. The module has five Form C relays rated at 1 amp each, 30V DC. It can be configured to function in either a zone relay mode or a common system mode.

When configured in the zone relay mode, relays energize when the associated IDC is in the alarm state. The module can be configured for activation by IDCs 1-5 or 6-10. One relay is automatically associated with each IDC.

When configured in the common system mode, relays energize or de-energize when the panel changes state. One relay is available for each of the following functions: Alarm, Supervisory, Trouble, Power and monitor.

The FSRRM mounts on a plastic snap track (included) or the FSRRM-S11 (optional) extended snap track. Each FSRRM-S11 holds up to 4 FSRRMs. Using either snap track the FSRRM can be installed in the MFC-A multifunction cabinet or another listed fire alarm enclosure. Panels will support two RRRMs of each configuration for a total of six on the 10-zone panel.

## SPECIFICATIONS

- > 18-12 AWG terminals
- > 18-27V DC
- > 2 3/4" W x 3 3/8" H x 1 1/2" D
- > Operating environment:  
temperature - 32-120F (0-49C);  
humidity - 93% RH, non-condensing