



Engineering Data

6306 NoCoax 4" Video Monitor

The Elvox® 6306 series monitors are designed to meet any requirement for videointercom security. Surface wall mounted on a steel back-plate (supplied). All monitors feature a crystal clear, hi resolution 625 lines, 4" B&W monitor, electronic tone signaling. Heavy duty coiled cord, door release, monitor activation, accessory push buttons. Brightness and contrast control. Door release indicator LED can be used to show status of entry doors provided with switch contacts. Other features include private conversation, restricted lock control, selective Coax or twisted pair video. Handset with electret microphone, provides clear duplex conversation.

General information

Specifications

-Low Profile Design

-4" 625 lines Resolution

-Nocoax Operation

-Private Conversation

-Tone Ring Signal

-Duplex Voice Operation

-Easy Surface Mount Wall Installation

-Door Status LED

-Tone ring volume selector with LED indication of "OFF"

System: Tone Ring Signal

Controls: Door Release (with Door Status LED)

Monitor Self Activation Auxiliary Function Brightness, Contract

Tone Ring Level(with LED "off" indicator)

Handset: Duplex Handset with electret Mic and

heavy duty coiled cord

Construction: Molded High Impact Plastic

Finish: White, Anthracite, Titanium

Wiring Terminations: Screw Terminal

Dimensions: 8.00" W., 8.75" H., 3.50" D.

Net Weight: 1 lb (.5 Kg)

Architects and Engineers Specifications

Apartment monitor station shall be Elvox® Model 6306. Monitor shall be designed for use in the NoCoax systems. Monitor shall be Surface mounted and shall include a high quality 4", high resolution 625 lines B&W picture Handset shall feature private duplex communication and electret microphone for exceptional voice fidelity. Handset shall include a heavy duty coiled cord. Monitor shall include a door release button, monitor self activation button, contrast/brightness controls, one (1) auxiliary control switch. LED door indicator shall be provided to provide positive confirmation of door release. Monitor shall be constructed of high impact ABS plastic in a soft white color (Anthracite, or Titanium optionally). Monitor shall allow for 3 tong ring volume settings and off with LED indicator. Monitor shall be desk mounted using optional desk adapter.

Lee Dan Communications, Inc.

www.leedan.com

info@leedan.com

800-231-1414

Specifications are subject to change without notice

oCoax 4" Video Monito

6306

REV 1.0

Form ED6306