

## DATA DISTRIBUTION BOXES

### APPLICATION

**For Private Use Only:** Salsbury 2400 (non-USPS approved) series data distribution system aluminum boxes have 1/4" thick extruded aluminum doors with a durable powder coated aluminum finish. Each door includes a 3/4" high door slot, a five (5) pin cylinder cam lock with two (2) keys and is hinged horizontally at the bottom. Alternative locking systems are available for options. Doors are available without slots upon request. The compartments have open backs (rear covers for a column of data distribution boxes #2451 are available as an option upon request) and are constructed of 20 gauge steel. All units have the same outside dimensions. Data distribution system boxes are designed to be installed between rack ladders (#2400).

The rack ladders support five (5) units to form a column of boxes. Data distribution system boxes can also be used in Free-Standing Mail Centers

### FEATURES

- Mix and Match 1, 2, 4 or 6-Door Modules
- Easy Rack Ladder Mounting
- Durable Powder Coated Finish
- With or Without Mail Slots

### DOOR SIZES

- 2401: 22"W x 11 1/2"H, 35 lbs, per cluster  
2401 Slots: 19 1/2"W x 3/4"H
- 2402: 22"W x 5 1/2"H, 35 lbs, per cluster  
2402 Slots: 19 1/2"W x 3/4"H
- 2404: 11"W x 5 1/2"H, 35 lbs, per cluster  
2404 Slots: 9"W x 3/4"H
- 2406: 11"W x 3 1/2"H x 15 1/2"D, 40 lbs, per cluster  
2406 Slots: 9"W x 3/4"H

### CLUSTER SIZES

- 2401, 2402: 23 1/4"W x 12 1/8"H x 15 1/2"Deep  
2404, 2406: Same as 2401, 2402

### REQUIRED COMPONENTS

- 2400 Rack Ladder - 1 or more, depending on grouping  
2413 Black Trim, 1 for each 3 columns



2401 1-Door Box



2402 2-Door Box



2404 4-Door Box



2406 6-Door Box

*Data distribution doors are available without slots as an option upon request and can accommodate combination locks #2486 (combination locks are not available on doors with slots and on #2401)*