

SURFACE MOUNT TELEPHONE ENTRY

APPLICATION

TekTone®'s Tek-ENTRY® Telephone Entry Systems are designed for easy operation and have a capacity of 1-750 suites with 7, 10 or 11 digit phone numbers.

FEATURES

- Weather- and vandal-resistant construction
- Use with rotary or touchtone service
- Memory retention during power failure (EEPROM)
- Programmable system master code
- Door timer cut-off feature • Multiple entrance capability
- Night service feature redirects all calls to guard station
- 26-bit Wiegand output to connect to card reader systems
- Secondary relay output
- Fire alarm input for emergency door release
- Unbreakable Lexan® Directory Window*
- Model TE-903A — Baked Enamel Finish
- Model TE-904 — Stainless Steel Finish
- Model TE-903ANP — No Phone Line version

SPECIFICATIONS

Dimensions: 11"W × 16"H × 2.65"D

Construction: 16-gauge Steel

Power Required: 110 VAC with PS-30A Transformers

Mounting: Standard Surface

REQUIRED COMPONENTS

TE-903A Baked Enamel Finish Entry Panel

-or-

TE-903ANP No Phone Line Entry Panel

-and-

PS-30A Transformer (2 required)

PM-900 No Phone Line Control Unit & Cabinet (for TE-903ANP only)

* Note: Lexan® is a Registered Trademark of the General Electric Corporation.



TE-903A / TE-903ANP
Telephone Entry

ARCHITECTS' AND ENGINEERS' SPECIFICATIONS

TekTone®'s Tek-ENTRY® Telephone Entry System is a complete automatic call and entry control system. The system operates on a standard dedicated telephone line and 110 VAC with 16 VAC transformer.

All units shall be surface mounted and constructed of 16 gauge steel and shall include a zinc diecast marine quality keypad, speaker/microphone, postal release option, and an RJ Plug Connector. Tek-ENTRY® allows for 1-750 suites with 7, 10 or 11 digit phone numbers.

Tek-ENTRY® TE903A with baked enamel finish shall include an integral 100 name directory with a Lexan® window.* The TE903ANP shall operate without a telephone line.