

TEK-ENTRY TELEPHONE ENTRY

APPLICATION

TekTone®'s Tek-ENTRY® Modular Series Telephone Entry Systems are designed for easy operation. All models have a capacity of 1-750 suites, and may be configured for 7-, 10- or 11- digit telephone numbers.

By entering a simple 4-digit code, the system calls the correct phone number to allow access. The called party's phone number remains secret. Programming and reprogramming are push-button simple.

FEATURES

- 3-year warranty (control unit only)
- Use with rotary or touchtone service
- Memory retention during power failure (EEPROM)
- 26-bit Wiegand output to connect to card reader systems
- Toll restrictor
- Front-panel programming
- Tamper-proof programming security
- Aluminum construction resists vandalism
- Unbreakable Lexan® Directory Window*
- Selectable 1-9 minute talk time limit

SPECIFICATIONS

Dimensions: Height: 19" (483 mm)
Width: refer to IL312 housing chart
Depth: .875" (22 mm) flush-mounted

Construction: Anodized extruded aluminum

Power Required: 110 VAC with PS-30A Transformers

REQUIRED COMPONENTS

AM-190D Directory Panel (60 names each max)
OF-190 Series Frame
OH-190 Series Housing
PS-30A Transformer (2 required)
TE-905A Modular Telephone Entry Panel

-or-

TE-905ANP No Phone Line version Telephone Entry Panel
TA-905 Optional Handset Panel

Suffix "P" Postal Release Option, installed

* Note: Lexan® is a Registered Trademark of the General Electric Corporation.



TE-905A / TE-905ANP
with AM-190D,
OF-192, OH-192

TE-905A / TE-905ANP

with TA-905 (Handset)
AM-190D (Directory)
OF-193 (Frame)
OH-193 (Flush Housing)



ARCHITECTS' AND ENGINEERS' SPECIFICATIONS

TekTone®'s Tek-ENTRY® Modular Series Telephone Entry System is a complete automatic call and entry control system. The system operates on a standard dedicated telephone line and 110 VAC with 16 VAC transformer.

All units shall include integral power supply, panel mounted PC board, metal telephone key pad, busy and door-open indication, postal release option and speaker/microphone panel, or optional armored handset. The Tek-ENTRY® Modular Series allows for a capacity of 1-750 suites, and may be configured for 7-, 10- or 11-digit telephone numbers.

The Tek-ENTRY® Modular Series System shall provide a relay output for controlling doors, gates, elevators, etc., and shall be able to dial either rotary or touchtone. It shall also provide built-in capability for multiple entrances. Construction shall be of extruded anodized aluminum modular panels.