



## Rotating Edwards Warning Siren

127 dB

## **EWS-11 Series**

## **FEATURES**

- > 127 dB @ 100 ft. (30.5 m)
- Maintenance free siren & rotating mechanism
- > Self-contained electrical connection spattery not included)
- > Powder coated exterior

## **SPECIFICATIONS**

- > 8 HP motor
- > Port tone freq.: 460 & 920 cps
- > Weight: 385 lbs. (174.6 kg)
- > Recommended batteries:
  - Group 27 sealed lead acid maintenance free (minimum)
  - GelCel or AGM Optima Blue Top Deep Cycle Marine

Featuring the industry's largest drive motor, this 8 HP, battery powered rotating siren delivers all the features one expects from a premium warning device.

Utilizing a 460 Hz tone, the EWS-11's low pitch is designed to penetrate structures and obstacles, making the warning area more complete. The EWS-11 features the same bullet-proof design and construction as other Edwards sirens. The EWS-11 uses top of the line, maintenance free rotating mechanisims and hand rolled, custom formed projectors.

All exposed siren components are of heavy gauge aluminum alloy and electro-plated, galvanized steel construction, which are "powder coated" for the most durable finish available.

The entire mass of the siren is centered over the pole so no stabilizing wires are required. Total shipping weight of the EWS-11 is 385 lbs. (174.6 kg).

Edwards is a registered trademark of GE Security

	of GE Security
ORDERING INFORMATION & ACCESSORIES	
Cat. No.	Description
EWS-11	Outdoor warning siren
EWS-H-1	Siren heater w/ thermostat
EWS-CDP-3 EWS-CDP-1 EWS-T-1	Three function siren control center Two function siren control center One function siren control center
ENC-H ENC-D	Radio control - hand held Radio control - desk mount
EWS-PMB EWS-PMB-SS	Utility pole mounting bracket - powder coat finish Utility pole mounting bracket - stainless steel finish

800-231-1414 • 631-231-1414 155 Adams Avenue • Hauppauge, NY 11788-3699 Fax 631-231-1498 • www.*LEEDAN*.com

INTERCOMS • MAILBOXES • DIRECTORIES
NURSE-CALL • ANNUNCIATORS • WIRE & CABLE

With continuous product improvement, specifications are subject to change without notice.