

NURSE-CALL HOUSING / CABINET

APPLICATION

The IH-151N Housing is used as a central junction point for wiring in the CM-800 and Tek-CARE® NC-110, NC-150, NC-200 systems.

Knockouts are included on all sides except lid to allow the connection of electrical conduit from any direction. In addition, the lid has a knockout which can be used to install an optional key lock—the TekTone® HW231 or equivalent.

A single-gang electrical junction box is mounted inside the main enclosure to allow protected electrical connections to be made. The enclosed electrical junction box is galvanized steel with a stainless steel cover plate.

FEATURES

- Maintenance free
- Easy Installation
- 19-gauge steel construction
- Knockouts provided
- UL® 1069 Listed when constructed with PK-151A Annunciator Power & Control Unit and SS-106 Transformer

SPECIFICATIONS

Dimensions: Height: 11.75" (300mm)
Width: 11.75" (300mm)
Depth: 3.75" (96mm)

Construction: 19 gauge, cold-rolled steel



IH-151N
Housing / Cabinet

ARCHITECTS' AND ENGINEERS' SPECIFICATIONS

Housing shall be TekTone® IH-151N housing or approved equal as supplied by LEE DAN®. The IH-151N housing shall be of steel construction for durability. It shall include a single-gang metal junction box to protect electrical connections.

Knockouts shall be provided on all sides except lid to facilitate easy connection of electrical conduit. The lid shall have a knockout for an optional key lock—TekTone® HW231 or equivalent.

All exposed surfaces shall be either stainless steel or painted to protect against oxidation. The outer enclosure shall be composed of 19-gauge cold-rolled steel.