

UL DUTY STATION

APPLICATION

The LI-150B Duty Station provides an indication of incoming calls in work areas away from the nurse call master station.

Normal calls are indicated by a steady light and intermittent tone.

Emergency calls take precedence and are indicated by a flashing solid-state LED light and a pulsating tone.

A tone-off switch permits silencing of the tone signal for normal calls only.

FEATURES

- UL® 1069 Listed
- Simple, reliable operation
- Call-placed indicator
- Mounted on rugged, flame-retardant (UL® 94V-0) plastic panel

SPECIFICATIONS

Dimensions: Height: 4.5" (114 mm)
Width: 2.75" (70 mm)
Depth: 1" (25 mm)
Projects: 0.5" (13 mm) from mounting surface

Construction: Reliable components mounted on a flame-retardant (UL® 94V-0) plastic faceplate

Connections: Screw terminals

Housing: Single gang ring (IH-357) with squarebox (IH-358), or exact equal.

REQUIRED COMPONENTS

Tek-CARE® NC-200, NC-150 or NC-110 Nurse Call System
IR-150 series or SF-100 series Patient Stations



LI-150B
Duty Station

ARCHITECTS' AND ENGINEERS' SPECIFICATIONS

Duty Stations shall be TekTone® LI-150B or approved equal as supplied by LEE DAN®. Both visual and audible indication of normal and emergency call shall be provided. A solid-state LED indicator shall provide a steady signal for normal calls and a flashing signal for emergency calls.

A **TONE OFF** switch shall be provided, which shall not be able to cancel an emergency signal. The station shall consist of reliable components mounted on a durable fireretardant (UL® 94V-0) plastic panel, and shall have screw terminals for electrical connections.

The LI-150B shall be UL® 1069 Listed.