

SUPPLEMENTAL POWER SUPPLY

APPLICATION

The PK305A (PK-305A) Supplemental Power Supply is used to provide additional power to the NC351A/2 Central Equipment to support 512 patient stations.

The supplemental power supply is housed in a durable metal enclosure with provisions for plug-in field wiring connections.

FEATURES

- UL® 1069 Listed
- Plug-in connectors for easy connection to NC351A/2 Central Equipment
- Provides additional power to the NC351A/2 Central Equipment to support 512 patient stations

SPECIFICATIONS

Dimensions: Console: 10.75" × 8.75" × 3.25"

Power Input: 115 VAC, 60Hz, 140W

Environments: 26°C, relative humidity maximum 80%

Terminations: Plug-on connectors

System protection: In-line fuses are provided on primary input

REQUIRED COMPONENTS

Tek-CARE® NC300II Nurse Call System
with NC351A/2 Central Equipment



**PK-305A
POWER SUPPLY**

ARCHITECTS' AND ENGINEERS' SPECIFICATIONS

The supplemental power supply shall be TekTone®'s PK305A (PK-305A) or approved equal as supplied by LEE DAN®. Supplemental power supply will include the necessary hardware to interface with TekTone®'s NC351A/2 Central Equipment to provide additional power to support 512 stations.

The supplemental power supply will be housed in a durable metal enclosure with provisions for plug-in field wiring connections.

The supplemental power supply shall be UL® 1069 Listed.