



9050 VEHICULAR SLIDE GATE OPERATOR

• RESIDENTIAL



- Electronic magnetic limits eliminate old style mechanical switches that can wear out, break or fail
- Automatic self-setting limits mean no limit switch adjustments – ever
- Safety – built-in mechanical and electronic reverse system
- Advanced microprocessor control board features programming switches to set the mode of operation required and has ports for DKS plug-in loop detectors to simplify wiring
- 5-year limited warranty



entrapment detection
reverses gate when obstructed



built in
power switch and reset switch



fail-safe release
never be locked out (or in)




unique design
allows easy access to all mechanical parts

9050 VEHICULAR SLIDE GATE OPERATOR

9050 1/2 HP

12" W x 24" H x 11.5" D (30.5cm W x 61cm H x 29.2cm D)



	CLASS OF OPERATION	MAX GATE LENGTH *	MAX GATE WEIGHT *	MOTOR	INPUT
9050 1/2 HP	I	16 Ft (4.9 m)	500 Lbs. (227 kg)	1/2HP Continuous Duty AC Motor	115 VAC, 60 HZ, 5.4A

* Assumes gate is on level ground, in good condition with properly adjusted hardware.
Other external factors may affect the performance of the gate operator.

Technical Features

Mechanical

Frame: G90 Galvanized steel to prevent rusting
Cover: Steel cover is plated and painted
Primary Reduction: Single cog belt
Speed: Approximately 10 in/sec (254 mm/sec)
Chain: Unit is shipped with 20-ft (6M) of #40 roller chain, chain brackets, hardware
Fail-Safe release standard

Options

Nickel or stainless steel chain
Base Plate for post mounting
Fail-Secure release kit

Electrical

Automatic limit adjustment
Auto-close timer 1-23 sec
Selectable stop / reverse loop function
Built in On / Off switch
Built in alarm reset switch
Two 115 VAC convenience outlets for accessory transformers
Automatically assumes fail-safe mode when an entrapment condition exists
Ports for plug-in open and reverse loop detectors.
DKS plug-in detectors only

Miscellaneous

Environmental: 10°F to 140°F (-12°C to 62°C)
Thermostatically controlled heater kit recommended for colder environments
External entrapment/obstruction sensing devices must be used with this operator
Shipping weight approximately 70 Lbs (31.8 kg)



Access Control Solutions since 1948

Distributed by:

Lee Dan Communications, Inc.
www.leedan.com
info@leedan.com
Toll-Free 1-800-231-1414

MEMBER:



DOOR KING, INC.

© 2014 All Rights Reserved. Product specifications may change without notice.
Rev. 2/14